


ULTRASONIC CLEANER

USER MANUAL



Thank you for purchasing this ultrasonic cleaner. Please take some time to read these operating instructions before use and keep them for future reference. Failure to follow these instructions may lead to serious artificial damages to the product.

ULTRASONIC PRINCIPLE



Ultrasonic cleaning is based on the cavitation effect caused by high frequency ultrasonic wave vibration signal in the fluid. Microscopic bubbles are formed, and then implode violently causing the cavitation which create an intense scrubbing action on the surface of the item being cleaned. The bubbles are small enough to penetrate microscopic crevices, cleaning them thoroughly and consistently.

Ultrasonic cleaning is extremely effective at removing dirt and grime which would normally require tedious manual cleaning by hand. It has been used to clean a wide variety of instruments and mechanical parts such as carburetors, returning them to almost "like new" condition without damage to delicate parts.

PREPARATION:

1. Carefully unpack the cleaner, remove all packing materials and check whether any parts have become loose or damaged during transit.

Contents:

a: Main machine

b: Sound proof lid

c: Power lead

d: Outlet filter

e: Mesh basket (Optional)

f: Manual

2. Place the cleaner on a flat, clean surface and ensure that the cooling fan will get adequate ventilation, and that all controls are set to off, and the drain tap is closed.
3. Ensure that the power lead is securely plugged into the cleaner, and that no part of the lead is likely to contact with moisture.
4. Carefully fill at least 1/2 of the tank with a solvent solution. Based on cleaning requirements, we recommend to use a small amount of cleaning solution because this will help increase the cleaning performance. Now the cleaner is ready for use.

Attention

While the machine is working normally, the synergy of the ultrasonic wave and tank gives a well-proportioned sound with no shudder on the surface of the water but sprays generated by the tiny bubbles. If there are discontinuous surges, please add or reduce a little of washing solution in the tank to stop the surges, which is good for get a better cleaning effect.

SAFETY PRECAUTIONS**Keep it away from children !**

This device can not be used by individuals with limited physical knowledge, or the mental disabled, or those lacking experiences or knowledge, such as children, unless they are supervised by an individual who can take charge of their safety or have received training in operating the device .

**Please read the following items very carefully as failure to comply with them may invalidate your guarantee**

- 1) DO NOT operate the unit without fluid in the tank. Always ensure that the fluid is no higher than the max mark and no lower than the minimum depth of 7cm.
- 2) DO NOT drop any item into the tank because it may damage the transducer. Always place items gently into the tank and use the basket whenever possible.
- 3) The more items you place in the cleaning bath, the less cleaning efficient you can get. Leaving enough spaces among items rather than overlapping them is recommended.
- 4) Do keep the lid closed during use. This will prevent splashes and reduce evaporation of the fluid.
- 5) Never immerse the machine or power cord in water or other liquid.
- 6) DO NOT touch the power plug with wet hands, especially when inserting or removing the plug.
- 7) DO NOT touch the unit if the machine has fallen into water during operation. Remove the power plug from the socket firstly.
- 8) DO NOT disassemble the machine if you are not professional.
- 9) UNPLUG the power source while filling or emptying the tank.
- 10) DO NOT spray water or liquid over the device and the control panel.
- 11) DO NOT operate the cleaner without proper grounding.
- 12) DO NOT place the device on a soft surface where the vents can be blocked.
- 13) Always turn the heater off after using as leaving it on can make the fluid evaporate and damage the internal components.
- 14) Take care when adding or removing items from the cleaning tank as the splashed fluid is likely to be hot and damage the internal components. Any splashed fluid must be dried immediately.
- 15) In case of emergency or failure to follow the aforementioned items, disconnect the main supply by turning off the switch on the back or removing the plug from the main socket.

FEATURES

Die casting stainless steel tank
Industrial grade integrated circuit
0~99°C temperature range
1 sec~99 min 59 secs or always on
LCD screen and power adjustable
Power cut memory function
Dewaxing and degreasing function
Degas, pulse, power and turbo sweep working mode
Auto Stand-by, Sleep, and wake up by one key-press Mode
Digital controller of high-precision and a long service-life

APPLICATIONS

This list is almost endless. Provided any stuff is non porous and can normally be immersed in water, they can be thoroughly cleaned. Here are some examples:

- Jewelry especially gold, silver & platinum
- Watchstraps
- Coins and other collectibles
- PCB Boards etc
- Engine/Model parts
- Toothbrushes & Dentures
- Electrical components
- Make-up cases
- Diesel injection pumps
- Printer heads and toner cartridges
- Motorcycle radiators
- Vehicle differentials
- Milking parlor equipment
- Golf clubs&grips&golf balls
- Horse bits&stirrups &horse brasses
- Tattoo needles
- Surgical equipment
- Motorcycle engine crank cases
- Engine cylinder heads
- Turbochargers
- Bicycle derailleurs
- Knives, bayonets and other militaria
- Gun and gun components
- Sundry laboratory use

Ultrasonic cleaning is not recommended to be used to clean the following gemstones:
Opal, Pearl, Emerald, Tanzanite, Malachite, Turquoise, Lapis and Coral.

OPERATION

1. Fill the stainless steel tank with cleaning solution; Plug the power lead into grounded outlet; Turns on the switch on the back of the ultrasonic cleaner and press the rotary power knob; After power-on, the LCD screen displays the preset temperature (25°C in default), actual environmental temperature, preset time (3 minutes in default), actual time, frequency and power ratio.
2. **POWER (ON/OFF):** The power knob can be used to turn on or off the machine by pressing the knob once, and to adjust the value of ultrasonic power from "0%" to "100%" by rotating the power knob. The power ratio can be displayed on the right bottom of the LCD screen.
3. **Cleaning modes: Common, Degas, Pulse, Turbo Sweep, Power Sweep.** Five cleaning modes can be chosen to clean different stuffs. Especially the power under each cleaning modes can be adjusted by rotating the power knob.
4. **Ultrasonic button:** The ultrasonic cleaning can be started or paused by pressing the "Ultrasonic" button once, and be stopped by keeping pressing the "Ultrasonic" button for a few seconds. The indicator will be on when ultrasonic cleaning works, while the indicator will be off and the machine will buzz when ultrasonic cleaning is finished.
5. **Time setting:** Press the ultrasonic "+/-" button once to add or decrease one second cleaning time; keep pressing the ultrasonic "+/-" button to make the time setting to be added or decreased by seconds, and by minutes after the second value has reached 59 seconds; press the ultrasonic "+" and "-" buttons simultaneously to make the machine enter into the "always on" working mode.
6. **Heating button:** The heating function can be started or stopped by pressing the "Heating" button once, while if the preset temperature is not 1~2°C higher than the actual temperature, the heating function can not be started. Under working mode, the heating function will start working automatically when the actual temperature goes down to a value which is 1~2°C lower than the preset temperature. In default, the heating function will stop automatically after the ultrasonic cleaning is finished.
7. **Temperature Setting:** 1°C can be added or decreased by pressing the heating "+/-" once, and the preset temperature can be added or decreased continuously by keeping pressing the heating "+/-" button.

NOTE: Do not pour water out until it's cooling, Hot water will hurt you and damage the machine itself.

DIFFERENT WAYS OF CLEANING

General Cleaning—use only water to clean under the temperature of about 50°C;

Enhanced Cleaning—add few drops of standard cleaning solutions, liquid soap, or detergent, or any other non-acidic cleaning agents.

Extensive Cleaning--removing tarnish, carbon & rust from non-plated metals, it is recommended to use specific cleaning solution associated with ultrasonic cleaners.

WARNING : Strong acid or alkaline cleaning solution will cause corrosion, rust and even puncture of tank or machine body. To solve this problem, please dilute the solution to mild PH or use a special tank made of a specific-graded stainless steel, like SUS304.

The cleaning solution will deteriorate in effectiveness over time and use. It is important to regularly change the fluid and carefully wash the inside of the cleaning tank in order to preserve the effectiveness and longevity of the cleaner. Do not use corrosive or abrasive cleaning tools to clean the tank which must be wiped down and dried before it can be re-connected to the electrical supply.

NOTE: If the machine starts to spark, smoke, smell of burnt electrics or displays any other fault the operator must immediately stop the machine, and isolate it from the electrical supply and contact the supplier. It is dangerous to use it after that.

Advantage

Ultrasonic is widely used throughout industries to remove difficult contaminants from the parts during or after manufacturing process which might require a stage of cleaning before the next process. In general, if an item can be cleaned with liquid, it can be cleaned much faster and more thoroughly with an ultrasonic cleaner. Compared with traditional solvent/scrubbing, our ultrasonic cleaners:

- Are more effective at removing contaminants;
- Are quicker to get a good cleaning effect;
- Save labor time of employees (and subsequent labor cost);
- can heat the cleaning solutions to a suitable cleaning temperature so as to enhance the cleaning efficiency;
- Have a digital controller of high-precision and a long service-life;
- Are of high performance;
- reduce chemicals in the cleaned stuffs;
- Are environment friendly because of its recyclability.

For Better cleaning effect:

- Immerse the cleaned stuffs well into the water. (below the "MAX" mark)
- Add a small amount of cleaning solution is added.
- Make sure that there is enough space around each stuff in the tank. The more stuffs you place in the tank, the less efficiency you can get. It is not advised to overlap stuffs because the ultrasonic cleaning system can not work well with layered stuffs.
- Use a basket. Do not put stuffs directly into the bottom of the tank because that is harmful for the inner tank. So it is better to use a suitable basket. Especially a metal basket only absorbs about 8% ultrasonic energy.
- Choose a suitable temperature: Generally, the higher the temperature is, the better cleaning effect the ultrasonic cleaner can make. However, when temperature exceed 70°C~80°C, cleaning effect will be affected. So the best temperature we suggest is 40°C~60°C.

SPECIFICATIONS

Model	Tank Size (mm)	Overall Size (mm)	Volume (L)	Power (W)	FREQ. (KHz)	Heating (W)	Time (min:secs)	Temp. (°C)
DK-600FTS	300x155x150	330x180x357	6.5	0~180	28/40/68	300	00:01-99:59	0-100
DK-1000FTS	300x240x150	330x270x357	10	0~240		300	00:01-99:59	0-100
DK-1500FTS	330x300x150	360x330x380	15	0~360		400	00:01-99:59	0-100
DK-2200FTS	500x300x150	550x330x357	22	0~480		500	00:01-99:59	0-100
DK-3000FTS	500x300x200	550x330x407	30	0~600		500	00:01-99:59	0-100

